

BEST AVAILABLE COPY

(12) PATENT ABRIDGMENT (11) Document No. AU-B-53681/86
(19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 586463

(54) Title
TILLAGE DISC AND ASSEMBLY

(51)* International Patent Classification(s)
A01B 015/16 A01C 005/06 A01C 007/20

(21) Application No. : 53681/86 (22) Application Date : 15.02.85

(23) Filing Date of Complete Specification : 14.02.86

(43) Publication Date : 21.08.86

(44) Publication Date of Accepted Application : 13.07.89

(60) Related to Provisional(s) : PG9316

(71) Applicant(s)
PYNARI NOMINEES PTY. LTD.

(72) Inventor(s)
GORDON FRANCIS LEIBLICH

(74) Attorney or Agent
R.K. MADDERN & ASSOCIATES

(56) Prior Art Documents
561553 14199/83 A01B
23898/84 A01B
33063/84 A01B

(57) Claim

1. A tillage disc having walls forming a convex outer side and a concave inner side, each of which is generally conical for portion at least of its area, said conical portion terminating in the disc periphery, the disc periphery of the convex and concave sides being joined by a bevel surface which slopes upwardly and inwardly, characterized in that a cutting edge is defined between the conical portion of the convex side of the disc and said bevel surface.

41
COPYRIGHT IN THE PATENT SPECIFICATION No.

COMMONWEALTH OF AUSTRALIA

PATENTS ACT 1952-1966

APPLICATION FOR A PATENT 60-

WE PYNARI NOMINEES PTY. LTD.

of Kimba, State of South Australia,
Commonwealth of Australia.

hereby apply for the grant of a Patent for an invention entitled "IMPROVEMENTS
IN TRASH FARMING IMPLEMENTS"

which is described in the accompanying provisional/~~complete~~ specification.

My/Our address for service is care of R. K. MADDERN & ASSOCIATES, Patent
Attorneys, 97^{1/2} King William Street, Adelaide, South Australia.
345

Dated this 15th day of February 1985

PYNARI NOMINEES PTY. LTD.,

By its Patent Attorneys,
R.K. MADDERN & ASSOCIATES.

R.K. MADDERN

TO:

THE COMMISSIONER OF PATENTS,
CANBERRA, A.C.T.

APPLICATION ACCEPTED AND AMENDMENTS

MAILED 19.5.89

(note: to be signed by the applicant(s), or if a Company, to be signed by a person on its behalf. Pat. inappropriate to a particular application should be cancelled).

COMMONWEALTH OF AUSTRALIA
Patents Act 1952-1969

DECLARATION IN SUPPORT OF AN APPLICATION FOR A PATENT OR PATENT
OF ADDITION

INSTRUCTIONS

Insert if available.
Full name(s) of
applicant(s).

In support of the Application
made by

PYNARI NOMINEES PTY. LTD

Title of invention.

for a patent/~~patent of addition~~ for an invention entitled

"IMPROVEMENTS IN TRASH FARMING IMPLEMENTS"

Full name(s) of
declarant(s).

~~I am~~ GORDON FRANCIS LEIBLICH

Address(es) of
declarant(s).

of Kimba, State of South Australia,
Commonwealth of Australia

do solemnly and sincerely declare as follows:—

~~1. I am/We are the applicant(s) for the patent/patent of addition~~

(or, in the case of an application by a body corporate)

1. I am/~~We are~~ authorized by the abovementioned applicant(s) for the patent/~~patent of addition~~
to make this declaration on its/~~their~~ behalf.

~~2. I am/We are the actual inventor(s) of the invention~~

(or, where a person other than the inventor is the applicant)

Full name(s) of actual
inventor(s).

2. GORDON FRANCIS LEIBLICH

Address(es) of actual
inventor(s).

of Kimba, State of South Australia,
Commonwealth of Australia

Recite manner in which
applicant(s) derive(s)
title from actual
inventor(s).

is/~~are~~ the actual inventor(s) of the invention and the facts upon which the applicant(s) is/~~are~~
entitled to make the application are as follows:—

By virtue of the provisions of Section 34(1) (fa)
of the Patents Act 1952-1979.

Declared at

Kimba

this

15th

day of

March

1985

Signature(s) of
declarant(s).

(Note: No attestation or
other signature is re-
quired).

G. F. Leiblich

To: The Commissioner of Patents,



COMMONWEALTH OF AUSTRALIA

PATENTS ACT 1952-62

COMPLETE SPECIFICATION

(ORIGINAL)

FEE \$1-M. C.V. 11/58
120
MAIL OFFICE

FOR OFFICE USE:

Application Number:
Lodged:

Class

Int. Class

53681/86.

Complete Specification Lodged:
Accepted:
Published:

Priority:

Related Art:

This document contains the
amendments made to
the original specification
relating to

TO BE COMPLETED BY APPLICANT

Name of Applicant:

PYNARI NOMINEES PTY. LTD.

Address of Applicant:

Kimba, State of South Australia,
Commonwealth of Australia

Actual Inventor:

GORDON FRANCIS LEIBLICH

Address for Service:

care of R.K. MADDERN & ASSOCIATES, 345
King William Street, Adelaide, South
Australia, 5000

Complete Specification for the invention entitled:

"IMPROVEMENTS IN TRASH FARMING
IMPLEMENTS"

The following statement is a full description of this invention, including the best method of performing it known to ~~the~~ us.

This invention relates to improvements in trash farming implements, and although it is not limited to the improvements in trash farming means and method the subject of our Australian Patent Application No.

5 14197/83, it is nevertheless particularly suited for use in a machine as described in that specification.

In that specification there was described and claimed a trash farming implement having tillage discs and soil replacement discs arranged in pairs across the
10 width of the machine, each tillage disc functioning to transport soil transversely, and each soil replacing disc functioning to replace that soil in the furrow cut by the tillage disc. One of the functions referred to in the specification was that of seeding, by passing
15 seed and superphosphate through a tube and deflecting the passage beneath the tillage disc. Using that machine for seeding had a very important advantage in that the seed depth below the soil was far more nearly constant than in prior art seeders using conventional seeding
20 machines.

While the configuration of the soil replacement disc does not appear to be very critical, it has been found that difficulties can be encountered with the tillage disc, and if a disc of curved cross-sectional
25 shape is used, there tends to be a build up of soil near the periphery of the disc on its convex side, which soil forms an annular ring adhering to the disc, which interferes with the smooth movement of soil transversely over the convex side thereof. Furthermore, the disc
30 is used on a much flatter angle than the usual disc and consequently if a conventional type disc is used, the bevelled edge is presented to the soil and this constitutes a very considerable resistance and the consequential considerable forces will cause blunting
35 of the sharp edge, and consequentially require more power to move the disc through the soil.

With the object of overcoming these difficulties,

in one embodiment of the invention the tillage disc has walls forming a convex outer side and a concave inner side, each of which is generally conical for portion at least of its area, said conical portion terminating in the disc periphery, the disc periphery of the convex and concave sides being joined by a bevel surface which slopes upwardly and inwardly, characterized in that a cutting edge is defined between the conical portion on the convex side of the disc and said bevel surface.

With this arrangement, the part of the disc which wears most by abrasion is the bevel, and consequently there is a self-sharpening effect at least to some degree, and further, there is an upward flow of soil over the conical outer face of the disc as the disc passes through the soil, this avoiding the otherwise quite serious cavitation which occurs due to soil build-up on a disc of the conventionally curved cross-sectional shape.

Although a machine constructed in accordance with the specification of the Australian Application No. 14197/83 is normally employed to have the same angle of inclination of rotation of the tillage disc no matter what soil it is used in, nevertheless there are different requirements for depth of planting of seed in different soils. As pointed out in that specification, the furrow which is cut is a shallow acute angled triangle in cross-section, and seed depth is unlikely to vary provided the seed is deflected into the furrow at approximately the same location. However that location will need to vary for different soil conditions and different moisture contents of the soil, and in an embodiment of this invention the bearing of each tillage disc surrounds a mounting tube from which depends a discharge conduit the discharge end of which is inclined to the axis of the tube, and locating means which fix the discharge conduit with respect to the tube in any selected one of a number of positions circumferentially displaced from one another around the axis of the mounting tube. This enables the discharge to be deflected to a selected place in the furrow which can be varied for different



planting depth requirements.

An embodiment of the invention is described hereunder.

In this embodiment, a tillage disc 10 for a machine of the type described in our said Australian Application No. 14197/83, is provided with conical walls 11 for most of its area, the walls being curved in cross-section only near the central hub 12. The disc is bolted to a bearing housing 13 containing bearings 14 and seals 15 in a bearing assembly 16 which is generally in accordance with known art. The bearings themselves surround and engage a mounting tube 17 through which an elbow-shaped discharge conduit 18 extends.

The edge 21 which is the sharp edge of the disc is the lower outer peripheral edge, and there is provided a bevel 22 on the concave underside of the disc which, in use, abrades the soil and the edge is thereby maintained sharp to some extent, and furthermore the bevel in being on the concave underside instead of the convex side does not present a bluff face to the soil as the disc traverses the soil.

The upper end of the mounting tube 17 is provided with a flat plate 24 and a pin 25 upstanding from that flat plate, and the discharge conduit 18 is a monolithic moulding of polyurethane or other elastomeric material which extends through the mounting tube 17, having a lower discharge end 26 which is angled to function as a deflector. The upper end has a flange 27 with a series of peripheral notches or slots 28 which are circumferentially spaced and extend radially inwardly, and these are arranged to selectively engage the upstanding pin 25. The angle of the discharge conduit can thereby be readily varied by simply deflecting the periphery of the elastomeric flange and repositioning it over the pin. Screw-threaded clamping means (not shown) can be used if required.

The machine is provided with a grain box and a superphosphate box, and delivery stars which are arranged

to deliver metered quantities of superphosphate and grain into respective conveyor tubes, each conveyor tube terminating at its lower end in a respective discharge conduit 18. By this means it is possible to use a
5 reduced amount of air flow, and in some instances to completely avoid air flow.

A consideration of the above embodiment will indicate that the invention is one of great simplicity but is nevertheless found to provide a marked improvement
10 over prior art.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A tillage disc having walls forming a convex outer side and a concave inner side, each of which is generally conical for portion at least of its area, said conical portion terminating in the disc periphery, the disc periphery of the convex and concave sides being joined by a bevel surface which slopes upwardly and inwardly, characterized in that a cutting edge is defined between the conical portion of the convex side of the disc and said bevel surface.

2. A tillage disc assembly comprising a tillage disc according to claim 1, a mounting tube, a bearing assembly between the tillage disc and mounting tube, a discharge conduit depending from the mounting tube and having a discharge end inclined with respect to the mounting tube, and locating means co-operable between the discharge conduit and the mounting tube in any selected one of a number of positions circumferentially displaced from one another about the axis of the mounting tube.

3. A tillage disc assembly according to claim 2 wherein said discharge conduit extends through the whole length of the mounting tube and wherein said locating means comprises an outstanding flange having a plurality of circumferentially spaced slots each extending radially inwardly from the periphery of the flange, there being a pin upstanding from, but fixed with respect to, the mounting tube, the conduit being rotatable within the mounting tube so that said slots are selectively positionable over said pin.

4. A tillage disc assembly according to claim 3 wherein said discharge conduit is of flexible and resilient material, and said slots are selectively positionable over said pin by deflection of said flange.




5. A tillage disc substantially as hereinbefore described with reference to and as illustrated in the accompanying drawings.

6. A tillage disc assembly substantially as hereinbefore described with reference to and as illustrated in the accompanying drawings.

Dated this 14th day of February, 1986.

PYNARI NOMINEES PTY. LTD.
By their Patent Attorneys
R.K. MADDERN & ASSOCIATES



1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200

201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300

FIG 1

53 681/86




FIG 2





FIG 3




FIG 4

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.